

# MAHINDRA IMPLEMENTS

**RUGGED CONSTRUCTION**

**HEAVY-DUTY COMPONENTS**

**EASY TO ATTACH AND USE**

Standard, Medium and Heavy-Duty Implements to meet your demands.



# Mahindra



## HEAVY-DUTY CUTTER PULL TYPE 15'

Recommended Minimum HP	50 HP
Hitch	Swivel Pivot
Deck Thickness	7 Gauge or 3/16"
Body Depth	9.5"
Side Skirt Material	1/4" x 12"
Underneath Deck	Heavily Braced, All Sections
Center/Wing Gearbox Rating	190 HP
Splitter Gearbox Rating	235 HP
Gearcase Power Rating	540 RPM - 1000 Optional
Blades	1/2" x 4"
Blade Tip Speed	15,342 FRM
Blade Overlap	6 1/2"
Blade Carrier (5-year Warranty)	3/4" Round Disc
Cut Width	180"

Overall Width	188"
Overall Length w/ Wheel	186"
Weight	5220 lb.
Cut Height	2" - 15"
Cutting Capacity	Up to 4"
Wheel Type	5 Lug STD Laminated
Row-width Adjustable	Yes
Suspension (Shock Absorbers)	Triple Spring
Wing Flex	90° Up - 22° Down
Input PTO	ASAE CAT 5 Constant Velocity
Wing Drive PTO w/ Slip Clutch	ASAE CAT 4
Skid Shoes	Replaceable
Chain Guards - Front & Rear	Standard
Tow Chains	Standard



## HEAVY-DUTY CUTTER LIFT TYPE 10'

Cutting Width	116"
Transport Width	122"
Type Hitch	CAT I or CAT II
Cutting Height	2"- 8"
Cutting Capacity	2" diameter material
Deck Thickness	3.063 or 7 GA steel
Side Bands	HD 8" channel
Minimum HP	52 HP
PTO Drive Shaft	Series 5 (with slip clutch)
Center Drive Shaft	Shock coupler protection
Stump Jumper	.625" thick round
Gear Boxes	Series 5 (with slip clutch)
Wheels	Shock coupler protection
Hub	.625" thick round
Front Chain Guard	Series 5 (with slip clutch)
Rear Chain Guard	Shock coupler protection
Weight	.625" thick round



## HEAVY-DUTY CUTTER PULL TYPE 10'

Cutting Width	116"
Transport Width	122"
Type Hitch	Center pull self leveling
Cutting Height	2"- 12"
Cutting Capacity	2" diameter material
Deck Thickness	3.063 or 7 GA steel
Side Bands	HD 8" channel
Tongue Jack	Fold up-removable
Minimum HP	42 HP
Hydraulic Cylinder	3 x 8 with hose
PTO	Constant velocity (with slip clutch)
Center Drive Shaft	Shock coupler protection
Stump Jumper	.625" thick round
Gear Boxes	100 HP center, 90 HP outboard
Tail Wheels	21" laminated
Spindle Hubs	Ball bearing
Front & Rear Chain Guard	Optional
Weight	1790 (lbs.)

WARNING: Whenever this machine is operated in populated areas or in other areas where thrown objects could injure persons or properties, safety chain shielding, to reduce the possibilities of throwing objects, must be installed.



## HEAVY-DUTY CUTTER LIFT TYPE 8'

Cutting Width	93"
Transport Width	98"
Type Hitch	CAT I or CAT II
Cutting Height	2"-8"
Cutting Capacity	2"-diameter material
Deck Thickness	10 GA steel
Side Bands	HD 7" channel
Minimum HP	42 HP
PTO Drive Shaft	Series 5 (with slip clutch)
Center Drive Shaft	Shock coupler protection
Stump Jumper	.625" thick round
Gear Boxes	100 HP center - high speed 90 HP outboard
Wheels	Laminated dual tailwheels
Hub	Bearings
Front & Rear Chain Guard	Optional
Weight	1205 (lbs.)



## HEAVY-DUTY CUTTER LIFT TYPE 5', 6', 7'

Top Link	Floating
Type Hitch	CAT II
Deck Thickness	3.063 or 7 GA steel
Side Bands	HD 8" channel
PTO Drive Shaft	Series 6 (with slip clutch)
Slip Clutch	Standard
Stump Jumper	.75" solid
Gear Boxes	90 HP
Wheels	Laminated dual tailwheels
Hub	Bearings
Front & Rear Chain Guard	Optional
Weight 5'	875 (lbs.)
Weight 6'	1205 (lbs.)
Weight 7'	1375 (lbs.)
Pull Type	Optional



## MEDIUM-DUTY CUTTER LIFT TYPE 5', 6'


Top Link	Floating
Type Hitch	CAT I
Deck Thickness	11 GA steel
Side Bands	HD 7" channel
PTO Drive Shaft	Series 4
Slip Clutch	Optional
Stump Jumper	.75" solid
Gear Boxes	90 HP
Wheels	Laminated
Hub	Regreaseable
Front Chain Guard	Optional
Rear Chain Guard	Optional
Weight 5'	615 (lbs.)
Weight 6'	755 (lbs.)
Pull Type	Optional



## STANDARD-DUTY CUTTER WITH HEAVY-DUTY CHANNEL LIFT TYPE 40'', 4', 5', 6'

Top Link	Floating
Type Hitch	CAT I
Deck Thickness	11 GA steel
Side Bands	HD 7" channel
PTO Drive Shaft	Series 4
Slip Clutch	Optional
Stump Jumper	Pan
Gear Boxes	40 HP
Wheels	Laminated
Hub	Regreaseable
Front & Rear Chain Guard	Optional
Weight 40"	390 (lbs.)
Weight 4'	436 (lbs.)
Weight 5'	510 (lbs.)
Weight 6'	645 (lbs.)
Pull Type	Optional

## BLADES FOR TOUGH JOBS



- Slide adjustment for tight spots
- 4', 5', 6', 7' models have 5 forward and 5 reverse angle positions
- Tilt feature for ditching
- 1/2" X 6" Reversible cutting edge



MAHINDRA 30 HP STANDARD BLADE

- 5', 6', 7' have 5 forward and 5 reverse angle positions
- Pin-Tilt adjustment for ditching
- Cat I hitch
- Moldboard height 13 1/2"
- 1/2" X 6" reversible cutting edge



- 5', 6', 7' models have 5 forward and 5 reverse angle positions
- Pin-Tilt adjustment for ditching
- Cat I hitch
- Moldboard height 15 1/2", extra reinforced
- 1/2" X 6" reversible cutting edge



MAHINDRA 70 HP HD BLADE

- 6', 7', 8' models have 5 forward and 5 reverse angle positions
- Pin-tilt adjustment for ditching
- Manual or hydraulic offsets
- Moldboard height 17 1/2"
- Cat I or II hitch



## STANDARD BOX SCRAPER

- Adjustable ripper shank
- Replaceable tips on shanks
- Dual reversible cutting edges
- 16" x 24" end plates
- Designed for maximum material volume
- Sizes 4', 5', 6', 7', 8'



## HEAVY-DUTY BOX SCRAPER

- Features all the above plus
- Extra heavy A-frame with clevis-type hitch
  - 1/2" thick end plates for extra cutting power and extended life
  - Sizes 5', 6', 7', 8'



## HEAVY-DUTY LANDSCAPE RAKE

- Soil preparation at its best
- 5/16" x 1" tempered tines
- H.D. 3/8" x 5" x 3" main frame
- Various angle positions
- Optional gauge wheels for depth control
- Sizes 4', 5', 6', 7', 8'
- Standard rakes also available with Slider Blade - Type A-frame and 4" x 4" x 5/16" main frame
- Sizes 4', 5', 6', 7w



## BALE FORK



## FRONT SPEAR

- Heavy wall tube construction
- 2" adjustable spear
  - Universal mounting brackets will fit most frontend loaders
  - Will fit 3-pt. hitch also
  - Available with penetrator pencil spear



## REAR SPEAR

- 2" Adjustable spear
- Available with penetrator pencil spear



## PALLET FORK

- 2500# capacity
- Adjustable tines made of reinforced channel
- Universal hookup will fit most tractor frontend loaders or 3-pt. hitch
- Standard head guard



## HEAVY-DUTY BOOM POLE

- 1800# capacity



## POTATO PLOW



## TILLER

- Heavy-duty cast iron gear box
- Slip clutch
- Long life hard carbon steel tines
- Replaceable skid shoes



**MAHINDRAUSA.COM**

The Mahindra Company ©2010 Mahindra USA, Inc.