

6000SERIES



EASY FRONT IMPLEMENT INSTALLATION

The 6000 series' advanced skid steer attachment system provides a faster, simpler approach to loader implement attachment and detachment.



DELUXE CAB

Each 6000 series model is available with a deluxe cab, fully equipped with air-conditioning, heater, a spacious interior, window wipers, flat deck ergonomic operator platform, and more.



EASY MAINTENANCE

The one-piece tilting hood allows for easy access to common service items. Simply unlock via a pulled lever. Servicing your tractor has never been simpler.

6000 SERIES ATTACHMENTS

TRACTOR	6065 2WD	6065 4WD	6065 4WD CAB	6075 4WD	6075 4WD CAB
LOADER MODEL		6075L	6075CL	6075L	6075CL
Standard Bucket Size [in]			78		
Maximum Lift Height [in]			133		
Dig Depth [in]			5.5		
Lift Capacity to Full Height at Pivot Pin [lbs]			3550		
Breakout Force [lbs]			5000		
Shipping Weight [lbs]			1880		
BACKHOE MODEL			65B		
Standard Bucket Size [in]			18		
Maximum Dig Depth [in]			112		
Dig Depth 2' Flat Bottom [in]			110		
Dig Force Bucket [lbs]			3895		
Dig Force Dipper [lbs]			2358		
Shipping Weight [lbs]			1100		



6000 SERIES SPECIFICATIONS

TRACTOR	6065 2WD	6065 4WD	6065 4WD CAB	6075 4WD	6075 4WD CAB
---------	----------	----------	--------------	----------	--------------

ENGINE

Type	Four-stroke, Turbocharged, Intercooled, Direct Injection, Water Cooled Diesel Engine				
Engine HP (kW) @ RPM	62 (46.2) @ 2100		71 (52.9) @ 2100		
Displacement [in ³ (cc)]	161.7 (2650)				
Number of Cylinders	3				
Bore & Stroke [in]	Bore: 3.78, Stroke: 4.8				
Fuel Tank [gal (L)]	23.8 (90.0)				

DRIVE TRAIN

Transmission	Full Synchro Mesh with Forward/Reverse Power Shuttle and Constant Mesh Range				
Number of Speeds	15F / 15R				
Clutch	Power Shuttle with Torsional Damper (wet)				
Brakes	Oil Immersed Brakes, Disc Diameter – 8.75 in. OD (222 mm), Ball and Ramp Type				

PTO

Type	2-Speed Independent Single Lever PTO				
Rear PTO RPM	540/540E				
PTO HP (kW)	53.5 (39.9)		61 (45.5)		

HYDRAULICS

Type	Open Center with Position and Draft Control, Telescoping Stabilizers and Flex Links				
Implement Pump Output [gpm (L/min)]	11.1 (42.0)				
Maximum Total Flow [gpm (L/min)]	15.7 (59.4)				
3-Point Hitch	CAT I & II				
Lift Capacity [lb (kg)]	4840 (2195)				

ELECTRICAL

Battery	12 V, 925 CCA				
Alternator	12 V, 55 A (External Fan)	12 V, 140 A (Internal Fan)	12 V, 55 A (External Fan)	12 V, 140 A (Internal Fan)	

DIMENSIONS

Overall Length [in (mm)]	141.7 (3599)	146.9 (3731)			
Overall Width [in (mm)]	73.2 (1859.2)	82.68 (2100)	78.74 (1999)	82.68 (2100)	
Overall Height [in (mm)]	104 (2641)	115 (2921)	105 (2667)	115 (2921)	
Wheelbase [in (mm)]	84.7 (2151.3)	87.4 (2219)			
Minimum Ground Clearance [in (mm)]	12.2 (309)	14.1 (358)			
Turning Radius [ft (m)]	11.5 (3.5)	12.4 (3.7)			
Weight [lb (kg)]	6095 (2764)	6746 (3059)	7495 (3399)	6746 (3059)	7495 (3399)

WHEELS & TIRES

AG [Front/Rear]	9.5L x 15 / 16.9 x 28	11.2 x 24 / 16.9 x 30			
IND [Front/Rear]	N/A	43 x 16-20 / 18.4-28			